

SCSIFlash™ SCSI1/SCSI250 pin Floppy Drive OEM Emulator to CF (SCSI Emulator for SCSI Drives)

Emulated Disk Sector sizes

256-4096 bytes

DESCRIPTION

The SCSIFlash™ is an integrated solution that utilizes proven SCSI drive architecture and industry-standard Compact Flash Card technology, providing a solid state, drop-in replacement for electro-mechanical hard drives.

The SCSIFlash™ is an industrial OEM grade solid state drive which allows Compact Flash (CF) cards of up to 128GB (host dependant) to be attached to a regular SCSI bus. It will be seen as a SCSI floppy drive by the host computer. The SCSIFlash™ can emulate many SASI, SCSI-1, or SCSI-2 drives and can be programmed to suit the host systems requirement. Emulated Disk Sector sizes can be 256, 512, 768, 1024, 2048, 4096 bytes.

The SCSIFLASH™ PCB allows service providers & OEM's to have a quick, low-cost flash memory solution for their legacy system through our configurable firmware that matches legacy systems software.

Benefit

- Firmware controlled by SCSI interface is adaptable to hosts' software SCSI drivers
- Provides a transparent interface from the SCSI bus to solid state Flash
- Eliminates the problems found in traditional electro-mechanical/magnetic media storage devices
- Fast, efficient field replacement
- Lower power consumption, noise and heat
- Fast write speeds
- Increased reliability
- Reduced unplanned downtime
- No additional software required for operation due to its SCSI data storage/bootable drive

FEATURES

- Small format PCB converts Compact Flash Media to appear as a floppy drive on a Host's SCSI bus
- 3.5" form factor PCB which will replace any 3.5" floppy drive or larger drives with adaptor
- Will fit in a 3.5" disk slot using the same mountings
- SCSI Host will typically see the device as a disk drive of any emulation
- Board is low power, using 5V only
- Microcode is field upgradable via integral USB port
- Optional integration support available if required

Solid State Disks Ltd manufacture, design & support sales of the SCSIFlash™ drive through our head office in Reading, United Kingdom.

The SCSIFlash™ is a recognised Trademark of Solid State Disks Ltd.

Solid State Disks
Ltd

Solid State Disks Ltd
The Granary
Hose Hill
Sulhamstead
Berks
RG7 4BB
United Kingdom
Tel: +44 (0) 118 9323 499
Fax: +44 (0) 118 9323 510
Email: info@ssd.gb.com
web: www.ssd.gb.com

SPECIFICATIONS



Board size:
3.5" Form factor – 3.75"x5.5"

Compact Flash:
Standard 3M header for Type 1 & 2 cards

Power:
5 Volts only @ 0.8 Watt (Typical) + CF requirement

Power connector:
Standard Disk drive type SCSI-1 and 2 Compatible. 50 pin DIL 0.1" Connector

SCSI transfer rate:
10Mbytes/second

USB Port for microcode load and real time diagnostics

Ethernet capability

Master Image (.img) /mirroring capability

Example Magneto Optic emulations:
DEC, Fujitsu, Hitachi, HP, IOMEGA, Konica, Maxoptix, Olympus, Pioneer, Ricoh, SONY, SYQUEST, TEAC.

Example systems available for fixed disk emulations:
Alcatel S12 & 1631, Alcatel-Lucent DACS III/IV, Applied Materials, AMAT, Cannon, DEC VAX, Encore, Evans & Sutherland, HP 9000 series 800, HP 9000 series 500, HP 9000 series 300, HP 1000 A Series, OMTI DTC51, Honeywell Measurex, MX-OPEN, Rosemount RS3, Sun Spark & Siemens EWSD.

Support covers the following Operating Systems:
HP-UX, HP-RTE, HPL, VMS, IRMX, OS/400, OMTI, GCOS, BOSS, VXworks, OS2, DEC VMS, RSTS, OSF, MXopen system QCs, UNIX, Solaris, Symbios Logic, SASI, Heller & VAX.



SCSIFLASH™ Drive front view